

SAFETY DATA SHEET

HD PAINT STRIPPER

Page: 1

Compilation date: 04/09/2013

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: HD PAINT STRIPPER

Product code: 1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Company name: Tensid UK Ltd
Unit 1 Carven Court
Canada Road
Byfleet
Surrey
KT14 7JI
United Kingdom

Tel: +44 (0)1932 564 133

Fax: +44 (0)1932 562 046

Email: info@tensid.com

1.4. Emergency telephone number

Emergency tel: +44 (0)1932 564 133

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion



Precautionary statements: P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

[cont...]

SAFETY DATA SHEET

HD PAINT STRIPPER

Page: 2

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P310: Immediately call a POISON CENTER/doctor/.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

POTASSIUM HYDROXIDE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-181-3	1310-58-3	-	Acute Tox. 4: H302; Skin Corr. 1A: H314	30-50%

DIPROPYLENEGLYCOL METHYLEETHER - REACH registered number(s): 01-2119450011-60

EINECS	CAS	PBT / WEL	CLP Classification	Percent
252-104-2	34590-94-8	Substance with a Community workplace exposure limit.	-	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Causes Burns. Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Seek medical attention if irritation or symptoms persist.

Eye contact: Causes burns. Bathe the eye with running water for 15 minutes. Remove contact lenses from the eyes before rinsing. Transfer to hospital for specialist examination.

Ingestion: Harmful if swallowed. Ingestion causes burns to the respiratory tract. Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Severe burns may occur.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Harmful if swallowed. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

[cont...]

SAFETY DATA SHEET

HD PAINT STRIPPER

Page: 3

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Turn leaking containers leak-side up to prevent the escape of liquid. Do not attempt to take action without suitable protective clothing - see section 8 of SDS.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Wash the spillage site with large amounts of water.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

[cont...]

SAFETY DATA SHEET

HD PAINT STRIPPER

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

POTASSIUM HYDROXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	2 mg/m ³	-	-

DIPROPYLENEGLYCOL METHYLETHER

EU	55 ppm; 308 mg/m ³	-	-	-
----	-------------------------------	---	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Gloves (alkali-resistant). PVC gloves.

Eye protection: Face-shield. Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Gel

Colour: Brown

Odour: Pungent

Evaporation rate: No data available.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Viscosity: Highly viscous

Boiling point/range°C: No data available.

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: >93

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: ~1.3

pH: >13

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

[cont...]

SAFETY DATA SHEET

HD PAINT STRIPPER

Page: 5

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Alkali metals. Finely powdered metals. Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

POTASSIUM HYDROXIDE

ORL	RAT	LD50	273	mg/kg
-----	-----	------	-----	-------

DIPROPYLENEGLYCOL METHYLEETHER

DERMAL	RBT	LD50	9150	mg/kg
ORAL	RAT	LD50	5135	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Severe burns may occur.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Harmful if swallowed. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

[cont...]

SAFETY DATA SHEET

HD PAINT STRIPPER

Page: 6

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
RAINBOW TROUT (<i>Oncorhynchus mykiss</i>)	96H LC50	39-56	mg/l

Hazardous ingredients:

POTASSIUM HYDROXIDE

Bacteria (<i>Photobacterium phosphoreum</i>)	15min EC50	22	mg/l
FISH (<i>Gambusia affinis</i>)	96H LC50	80	mg/l
FISH (<i>Poecilia reticulata</i>)	24H LC50	165	mg/l

DIPROPYLENEGLYCOL METHYLEETHER

DAPHNIA	48H EC50	1919	mg/l
FISH	96H LC50	10000	mg/l
GREEN ALGA (<i>Selenastrum capricornutum</i>)	96H LC50	> 969	mg/l

12.2. Persistence and degradability

Persistence and degradability: Readily biodegradable. Greater than 60% biodegradable according to method OECD 301.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Soluble in water. Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: The product may affect the acidity (pH factor) in water with risk of harmful effects to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

SAFETY DATA SHEET

HD PAINT STRIPPER

Page: 7

Section 14: Transport information

14.1. UN number

UN number: UN1814

14.2. UN proper shipping name

Shipping name: POTASSIUM HYDROXIDE SOLUTION

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.