

PRODUCT DATA

tensid[®] uk ltd

AGS Graffi Coat 103 Street Scene

Fine textured anti-graffiti & anti-sticker coating

Description and use

AGS Graffi Coat 103 Street Scene is a high solids, and high performance non-sacrificial polysiloxane, textured, anti graffiti coating, as well as an anti sticker and fly poster coating, available in clear gloss and in most BS. RAL and NCS colours.

Suitable for application to most non absorbent surfaces which are normally painted, such as wood, metal, plaster and concrete. Ideal for bollards, junction boxes, lamp posts etc, in the Street Scene.

Advantages

- Long lasting 25-30 years can be expected.
- 95% solids
- Extremely resistant to most graffiti markers
- Tested to be resistant to more than 25 cycles of removals.
- Adhesion resistant properties against stickers, fly posting and chewing gum.
- Easy application with brush, roller or spray
- One coat only
- Economical
- Environmentally responsible VOC 37 grams P/L
- Fast drying
- Isocyanate free

Limitations

- Not suitable on brick or natural stone if permeability is important.

Preparation

Protect surrounding surfaces.

Do not apply in temperatures below 5° C or above 30°C.

If in doubt contact Tensid Technical Department.

Equipment

Apply with a brush, roller or spray.

TECHNICAL DATA

Appearance: N/A

pH Value: N/A

Description: 95% solids polysiloxane

Pretesting

Always test each type of surface to ensure suitability and desired results. Apply test area according to the following application procedures.

Application Instructions

1. Clean the surface carefully rub the surface lightly with sandpaper, prime with suitable primer if necessary .
2. Whilst stirring base, slowly add all the curing agent.
3. Apply to a wet film thickness of 80 micron to achieve a 75 micron dry film thickness.
4. Pot life, 4 hours. Do not re-seal mixed product.
5. Drying time at 20°C.
Touch Dry:- 2-3 Hours.
Firm Dry : - 7 – 8 Hours.
6. Full Anti Graffiti will be achieved after 7 days.

Graffiti Removal

Remove graffiti using Graffi Green (please refer to Data Sheet) on a dampened cloth and wipe off . Neutralise with water, preferably with a few drops of ordinary detergent.

Coverage Rates

Theoretical Coverage:- 10-12 m² per litre.
Coverage rates will vary according to the surface, texture and application method.

Packing

Base Component – 4 Litres. Activator -1 litre or
Base Component – 1 Litre. Activator - 250 ml.

Safety Information

Wear suitable PPE – goggles and gloves to avoid splash to bare skin or eyes. Always refer to material safety data sheet before use.

Storage and Shelf Life

Graffi Coat 103 Street Scene may be stored for 2 years in tightly sealed unopened containers. Store in good conditions within not below 5°C or above 30°C. Protect from frost.

This Product Data is compiled to be of assistance but is without guarantee. Users are responsible for safe working practices. Always refer to Material Safety Data Sheets (MSDS) for full information before using this product.

For more information and photos please visit:

www.tensid.com

Share your project photos and news on the Tensid UK social media professional community pages:



tensid[®] uk ltd

AGS Graffi Coat 103 Street Scene

REVISION: 01 July 2015, N^o.2