

PRODUCT DATA

tensid[®] uk ltd

Oil Stain Remover Poultice

Effective and safe on most masonry

Description and use

Oil stain remover poultice is a powerful and easy to use oil and grease stain remover, fast and effective, suitable for most masonry

Advantages

- Ready to use no mixing
- Effective on most types of oil
- Fast acting

Limitations

- Slight odour

Pretesting

Test product in an inconspicuous area if compatibility with the surface is doubtful.

Application Instructions

Shake Well Before Use

1. Remove any visible not penetrated oil or grease
2. Apply the product by pouring it on to the stain, aim to have a product thickness of 4-5 mm
3. Distribute evenly with a brush if required
4. Allow to dry completely on the surface until a white dry powder appears
5. Remove the dried product
6. Reapply If the stain persists
7. Rinse with clean water preferably warm

TECHNICAL DATA

Appearance: White/grey paste

pH Value: N/A

Boiling Point:

Coverage

1 to 3 sqm per litre

Packing

500 ml plastic bottles

Safety Information

Causes irritation. Wear suitable PPE goggles and gloves to avoid splash to bare skin or eyes.

Always refer to material safety data sheet before use

Shelf Life

Up to 30 months in a sealed container

This Product Data is compiled to be of assistance but is without gurantee. Users are responsible for safe working practices. Always refer to Material Safety Data Sheets (MSDS) for full information before using this product.

For more information and photos please visit:
www.tensid.com

Share your project photos and news on the Tensid UK social media professional community pages:



tensid[®] uk ltd
Oil Stain Remover Poultice

REVISION: 01 July 2015, N^o.2