

PRODUCT DATA

tensid[®] uk ltd

Impreg Dust Binder

Durable Dustbinder

Description and use

Impreg Dust Binder is a waterborne acrylic copolymer surface dust binding treatment. This easy to use, low VOC, low odour product provides a clear finish for use on concrete and masonry surfaces.

Advantages

- Low odour
- Long lasting material suitable for interior and exterior applications.
- Fast drying – reduces down time
- Provides a level of permeability

Limitations

- Not suitable for application to surfaces that are heavily laden with oils.
- Not suitable for application to wet and saturated areas
- Not suitable for surfaces subjected to below grade water exposure.
- Not suitable for use on non porous surfaces
- Limited effectiveness on non masonry surfaces
- May darken substrates

Preparation

Protect surrounding surfaces and beware of wind drift. Remove all dirt and surface contaminants. Rinse thoroughly to remove all cleaning compounds and residues. Allow surfaces to dry thoroughly before application.

Surface and air temperatures should be a minimum of 5°C and expected to remain so for 4 hours following application. Surface and air temperatures should not exceed 30°C. On warm days, apply early in the morning and to shaded areas.

TECHNICAL DATA

Appearance: White liquid

pH Value: 5.5 - 7

Boiling Point: N/A

Equipment

Apply using a low compression sprayer or brush

Pretesting

Always test each type of surface before overall application to ensure suitability and desired results. Allow test application to dry thoroughly before inspection.

Dilutions

Apply Impreg Dust Binder as packaged. Do not alter or blend with other materials. Stir or mix well before use.

Application Instructions

1. Remove all surface contaminants
2. Apply to a visibly dry surface
3. For best results apply using low compression sprayer. The product can also be applied by brush.
4. A single saturating coat is normally sufficient however if testing determines a 2 coat system is required the second coat should be applied prior to the first coat drying.

Coverage

Estimated coverage is 4 - 6 m² per metre

Drying Time

The product should be touch dry in 1 hour. Avoid contact with water for a minimum of 24 hours.

Packing

1 x 25 litre plastic container.

Safety Information

May cause irritation. Wear suitable PPE – rubber gloves to avoid splash to bare skin or eyes. Always refer to material safety data sheet before use.

Shelf Life

Impreg Dust Binder may be stored for up to 12 months in a tightly sealed, unopened container.

This Product Data is compiled to be of assistance but is without guarantee. Users are responsible for safe working practices. Always refer to Material Safety Data Sheets (MSDS) for full information before using this product.

For more information and photos please visit:

www.tensid.com

Share your project photos and news on the Tensid UK social media professional community pages:



tensid[®] uk ltd

Impreg Dust Binder

REVISION: 01 July 2015, N^o.2