

PRODUCT DATA

tensid[®] uk ltd

Driklean

Latex Film Cleaner

Description and use

DriKlean is a latex cleaning compound for most types of masonry, such as marble, limestone, terracotta, sandstone, concrete and plasters, designed mainly for interior cleaning where traditional cleaners cannot be used safely and where rinsing may be impractical. Can be sprayed, brushed or roller applied. Surface soiling such as dust, soot, and grease is absorbed into the latex film and contained. When dry, normally within 24 hours, the film and contamination is peeled off in sheets for safe and easy disposal.

Advantages

- Safe to use on sensitive surfaces
- Easily peeled off
- User friendly
- Low odour
- Near neutral pH

Limitations

- Not for use on gilded surfaces
- Product efficiency is reduced when temperatures are below 4°C and above 30°C

Dilutions

Use in concentrate. Do not dilute or alter and stir thoroughly before use. Keep container tightly sealed until ready to use.

Pretesting

Always test each type of surface to ensure suitability and desired results

Equipment

Brush, heavy nap roller, or hopper type airless sprayer fitted with chemical resistant fittings and a minimum tip size of 0.027 – 0.031 inches

TECHNICAL DATA

Appearance: Pale yellow paste

pH Value: 9 - 10

Boiling Point: N/A

Application instructions

- 1.Mask off areas not to be cleaned with polythene film, work in sections not larger than 3 m x 3 m to facilitate easy removal. Stir thoroughly before application.
- 2.Using hopper sprayer, brush or roller, apply in a generous even coat of approximately 2 to 4mm wet. Do not atomize if spraying
NOTE: Extremely porous masonry or roughly textured masonry may require 2 coats to ensure ease of peeling.
- 3.Allow DRIKLEAN to dry completely
DRIKLEAN dries and is ready to peel in approximately 4 to 6 hours but may take up to 24 hours depending on film thickness, temperature and humidity.
- 4.Starting at one edge, pull the dried film from the surface and dispose of in accordance with local Regulations.

Cleaning of spray equipment and tools

Clean tools and equipment with soap and water, Take extra care to clean spray equipment thoroughly.
Dried material may simply be peeled off.

Coverage rates

1 - 5m² depending on porosity of the substrate.
Expect higher consumption on detailed and intricate features.

Packing

1 x 10 litre plastic container

Safety Information

Wear suitable PPE – goggles and gloves to avoid splash to bare skin or eyes.
Always refer to material safety data sheet before use.

Shelf Life

DRIKLEAN may be stored for up to 1 year in a tightly sealed, unopened container and in a frost free environment. Published shelf life assumes upright storage of factory sealed container in a dry place maintaining temperature of 7°C to 30°C.

This Product Data is compiled to be of assistance but is without gurantee. Users are responsible for safe working practices. Always refer to Material Safety Data Sheets (MSDS) for full information before using this product.

For more information and photos please visit:

www.tensid.com

Share your project photos and news on the Tensid UK social media professional community pages:



tensid[®] uk ltd

DriKlean

REVISION: 01 July 2015, N^o.2